


**Document of Performance  
According to Regulation (EU) 305/2011**

|  |  |                 |
|--|--|-----------------|
| Aduro 17 Series  |  | DoP No: 17 0001 |
| Roomheater burning solid fuel <u>without</u> hot water supply.<br>EN 13240:2001/A2:2004/AC:2007  |  |                 |
| Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. <a href="http://www.aduro.dk">www.aduro.dk</a> , <a href="mailto:info@aduro.dk">info@aduro.dk</a> , Tel.: +45 70274703.       |  |                 |
| System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control. |  |                 |
| Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 1235.  |  |                 |
| performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> :  |  |                 |
| 300-ELAB-2323-EN<br>300-ELAB-2323-NS   |  |                 |
| Declared performance   |  |                 |
| <b>Harmonized technical specification</b>  | <b>EN 13240:2001/A2:2004/AC:2007</b>   |                 |
| <b>Essential characteristics</b>   | <b>Performance</b>   |                 |
| <b>Fire safety</b>   |  |                 |
| Reaction to fire   | A1   |                 |
| Distance to combustible materials  | Minimum distances, in mm<br>rear = 75<br>sides:<br>- with side glass = 700<br>- without side glass = 400<br>front = 1000 |                 |
| Risk of burning fuel falling out   | Pass   |                 |
| <b>Emission of combustion products Wood</b>  | CO[0.09 %]   |                 |
| <b>Surface temperature</b>   | Pass   |                 |
| <b>Electrical safety</b>   | NPD  |                 |
| <b>Cleanability</b>  | Pass   |                 |
| <b>Maximum water operating pressure</b>  | NPD  |                 |
| <b>Flue gas temperature at nominal heat output Wood</b>  | T [283°C]  |                 |
| <b>Mechanical resistance (to carry a chimney/flue)</b>   | NPD  |                 |
| <b>Thermal output</b>  |  |                 |
| Nominal heat output Wood   | 7,0 kW   |                 |
| Room heating output  | 7,0 kW   |                 |
| Water heating output   | *** kW   |                 |
| <b>Energy efficiency Wood</b>  | $\eta$ [78 %]  |                 |

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS  
Hasselager, 27-10-2020



.....